

# EQUIPMENT

Users are reminded that the here below indicated **dimensions** and **capacities** may vary, because of slight manufacture differences even by the same manufacturer.

So that **Trailer SpA** can't be considered responsible about the mismatch between what is indicated and the real dimensions of your container.

**Limits:** Remember that certain ports or destinations have weight limits that are even lower than the gross weight of the containers.

## CONTAINER 20' BOX



<b>WEIGHT</b>	tare	2050-2650 kg			
	maximum payload	18270-27980 kg			
<b>DIMENSIONS</b>	<b>outside</b>	<b>inside</b>	<b>doors</b>		
	length	6058 mm	5860 mm		
	width	2438 mm	2310 mm	2280 mm	
	height	2591 mm	2360 mm	2270 mm	
<b>CAPACITY</b>	32.00 / 33.90 m <sup>3</sup>				

## CONTAINER 40' BOX



<b>WEIGHT</b>	tare	3630-3740 kg			
	maximum payload	26740-26850 kg			
<b>DIMENSIONS</b>	<b>outside</b>	<b>inside</b>	<b>doors</b>		
	length	12192 mm	12010 mm		
	width	2438 mm	2300 mm	2290 mm	
	height	2591 mm	2360 mm	2260 mm	
<b>CAPACITY</b>	65.20 / 67.70 m <sup>3</sup>				

## CONTAINER 40' HIGH CUBE



<b>WEIGHT</b>	tare	3800-4150 kg			
	maximum payload	26580-26600 kg			
<b>DIMENSIONS</b>	<b>outside</b>	<b>inside</b>	<b>doors</b>		
	length	12192 mm	12010 mm		
	width	2438 mm	2340 mm	2290 mm	
	height	2896 mm	2680 mm	2570 mm	
<b>CAPACITY</b>	75,70 / 76,00 m <sup>3</sup>				

## CONTAINER 20' OPEN TOP



<b>WEIGHT</b>	tare	2150-2250 kg				
	maximum payload	18170-27980 kg				
<b>DIMENSIONS</b>	<b>outside</b>	<b>inside</b>	<b>doors</b>	<b>roof opening</b>		
	length	6058 mm	5800 mm	5700 mm		
	width	2438 mm	2310 mm	2280 mm	2150 mm	
	height	2591 mm	2280 mm	2010 mm		
<b>CAPACITY</b>	31,40 / 32,60 m <sup>3</sup>					

## CONTAINER 40' OPEN TOP




<b>WEIGHT</b>	tare	3650 kg				
	maximum payload	26680 kg				
<b>DIMENSIONS</b>	<b>outside</b>	<b>inside</b>	<b>doors</b>	<b>roof opening</b>		
	length	12192 mm	12020 mm	11800 mm		
	width	2438 mm	2320 mm	2280 mm	2150-2190 mm	
	height	2591 mm	2280 mm	2190 mm		
<b>CAPACITY</b>	64,00 / 66,40 m <sup>3</sup>					

## CONTAINER 20' FLAT RACK



<b>WEIGHT</b>	tare	2300-2560 kg			
	maximum payload	17850-27920 kg			
<b>DIMENSIONS</b>	<b>outside</b>	<b>length between end walls</b>	<b>open side</b>		
	length	6058 mm	5660/5930 mm	5500/5700 mm	
	width	2438 mm	<b>width of the loading floor</b>	2390 mm	
			<b>width between internal supports</b>	2230/2250 mm	
height	2591 mm	<b>internal height</b>	2200/2285 mm		

## CONTAINER 40' FLAT RACK



<b>WEIGHT</b>	tare	2700 kg			
	maximum payload	21300-31030 kg			
<b>DIMENSIONS</b>	<b>external</b>	<b>length between end walls</b>	<b>open side</b>		
	length	12192 mm	12080 mm	11800 mm	
			<b>width of the loading floor</b>	2430 mm	
	width	2438 mm	<b>width between internal supports</b>	2230/2240 mm	
height			2591 mm	<b>internal height</b>	1850/2100 mm

## CONTAINER 20' REEFER



<b>WEIGHT</b>	tare	2800-3150 kg			
	maximum payload	17090-27280 kg			
<b>DIMENSIONS</b>	<b>outside</b>	<b>inside</b>	<b>doors</b>		
	length	6058 mm	5330 mm		
	width	2438 mm	2220 mm	2165-2285 mm 7'1"-7'6"	
height	2591 mm	2135-2260 mm 7'-7'5"	2150-2210 mm 7'-7'3"		
<b>VOLUME</b>	26,2 / 28,3 m <sup>3</sup>				
<b>TEMP. RANGE</b>	-25 / +25 °C				

## CONTAINER 40' REEFER



<b>WEIGHT</b>	tare	3900-4600 kg			
	maximum payload	25080-25980 kg			
<b>DIMENSIONS</b>	<b>outside</b>	<b>inside</b>	<b>doors</b>		
	length	12192 mm	11180 mm		
	width	2438 mm (8')	2240 mm	2180 mm	
height	2591 mm	2175 mm	2110 mm		
<b>VOLUME</b>	54,90 m <sup>3</sup>				
<b>TEMP. RANGE</b>	-25 / +25 °C				